

## Product Data Sheet

### SL-10 OIL CAN LUBRICANT™

Heavy-Duty Lubricant, Penetrating Oil & Rust Inhibitor

#### General Information

- A blend of high-quality, oil-rich ingredients
- Contains MPC's MT-10 Metal Treatment™ technology for increased boundary film lubrication
- Contains MPC's PL-10 Power-Lift Grease™ (lithium complex grease) for enhanced lubrication qualities
- Contains no PTFE, silicone, graphite, moly or solid lubricants

#### Key Features & Benefits

- Provides long-lasting protection against rust & corrosion
- Protects against extreme humidity environments
- Quick lubricating & penetrating action
- Creeps into remote, normally inaccessible areas
- Provides free-flowing protection

#### Typical Applications

- Metal mechanisms
- Sleeve bearings
- Metal-to-metal surfaces
- Open gears
- Chain drives
- Steel cables
- Drag lines
- Couplings
- Bushings
- Linkages

- Pulleys
- Wheels
- Hinges
- Augers
- Tools
- Any other automotive, industrial or commercial areas of lubrication that require an external spray lubricant for accessible or hard-to-reach areas.

#### Availability

- 16-oz. plastic bottles\*
  - 1-gallon & 5-gallon containers
  - 15-gallon & 55-gallon drums
- \* Trigger (pump) sprayers sold separately.

#### Directions for Use

Shake or mix contents of container well. Wipe off exposed surfaces. Apply SL-10 Oil Can Lubricant™ directly to areas to be lubricated. Repeat in especially stubborn applications.

#### Typical Properties

Flash Point ..... 295°F (146.1°C) D93  
Specific Gravity @ 60°F, g/cm<sup>3</sup> ..... 0.933  
Density ..... ~ 7.786 lbs. per U.S. gal.  
Viscosity @ 100°C, cSt ..... ~ 5.1  
Timken Extreme Pressure OK Load ..... 60+  
Odor ..... Mild petroleum  
Color ..... Milky amber  
Appearance ..... Low viscosity liquid  
Solubility in Water ..... Insoluble

## Health & Safety

**CAUTION!** May cause eye and skin irritation. Aspiration hazard if swallowed – can enter lungs and cause damage.

**WARNING!** Slipping hazard if spilled.

Consult Material Safety Data Sheet (MSDS) for additional information.

## U.S. DOT Freight Classification

- Identification Number: Not regulated.
- Proper Shipping Name: Lubricant oil.
- Hazard Class: Not applicable.
- Packing Group: Not applicable.



***“The Strength in Lubrication”<sup>®</sup>***

752 Kilgore Road  
Jackson Center, PA 16133 U.S.A.

Phone: 800-227-7049

814-786-0166

Fax: 814-786-7321

Website: [www.mpclubricants.com](http://www.mpclubricants.com)